

CLAIMS

What is claimed is:

- 5 1. An information handling system, comprising:
 a processor for coupling to a memory;
 a connector for receiving a removable wireless device;
 a fixed network controller;
 an indicator, shared between the wireless device and the network controller,
10 for indicating multiple non-zero communication speeds of the wireless device, and
 for indicating multiple non-zero communication speeds of the network controller.
2. The system of claim 1, wherein at least one communication speed of
 the network controller is different from the communication speeds of the wireless
15 device.
3. The system of claim 1, wherein at least one communication speed of
 the wireless device is different from the communication speeds of the network
 controller.
20
4. The system of claim 1, wherein the communication speeds of the
 wireless device include at least three communication speeds.
5. The system of claim 1, wherein the communication speeds of the
25 network controller include at least three communication speeds.

6. The system of claim 1, wherein the indicator is a first indicator, and comprising:

a second indicator, shared between the wireless device and network controller, for indicating network activity.

5

7. The system of claim 1, wherein the indicator is for indicating a working wireless network connection and for indicating a working wired network connection.

8. The system of claim 1, wherein the indicator includes at least first and second indicators for indicating the communication speeds.

10

9. The system of claim 1, and comprising:
status processing logic for overriding the wireless device sharing of the indicator when the network controller is connected to a wired network, so that access to the indicator is provided to the network controller instead of the wireless device.

15

10. The system of claim 1, wherein the indicator is integrated in a wired connector.

20

11. The system of claim 1, wherein the network controller is fixably attached to a motherboard.

12. The system of claim 1, wherein the connector is fixably attached to a motherboard, and wherein the wireless device is removably attachable to the connector.

25

13. The system of claim 1, wherein the connector is a mini-PCI connector.

14. The system of claim 1, wherein the wireless device is a mini-PCI wireless card.

15. A method of operating an information handling system that includes a processor for coupling to a memory, a connector for receiving a removable wireless device, and a fixed network controller, the method comprising:

between the wireless device and the network controller, sharing an indicator for indicating multiple non-zero communication speeds of the wireless device, and for indicating multiple non-zero communication speeds of the network controller.

16. The method of claim 15, wherein at least one communication speed of the network controller is different from the communication speeds of the wireless device.

17. The method of claim 15, wherein at least one communication speed of the wireless device is different from the communication speeds of the network controller.

18. The method of claim 15, wherein the communication speeds of the wireless device include at least three communication speeds.

19. The method of claim 15, wherein the communication speeds of the network controller include at least three communication speeds.

20. The method of claim 15, wherein the indicator is a first indicator, and comprising:

between the wireless device and network controller, sharing a second indicator for indicating network activity.

PATENT

Docket No.: 16356.765 (DC-03294A)

Customer No. 000027683

21. The method of claim 15, wherein sharing the indicator comprises:
sharing the indicator for indicating a working wireless network connection and
for indicating a working wired network connection.

5 22. The method of claim 15, wherein sharing the indicator comprises:
sharing at least first and second indicators for indicating the communication
speeds.

23. The method of claim 15, and comprising:
10 overriding the wireless device sharing of the indicator when the network
controller is connected to a wired network, so that access to the indicator is provided
to the network controller instead of the wireless device.